

9081/GA Fireguard Evolution

FIRE FIGHTERS

Available also as no-antistatic version - A30 - ART. 9081G



LEATHER TRANSPARATION
+400%

HEAT INSULATION
+30%

LONG LASTING SOLE
+40%

SOLE BONDING STRENGTH
+90%

HEEL ENERGY ABSORPTION
+100%

- The ultimate fire-fighters boot.
- High visibility PPE, lightweight and comfortable
- Ankle protection, side antiperforation panels and abrasion-resistant rubber overcap.
- Good stability both for walking and running
- Lining: GORE-TEX® Performance Comfort footwear, excellent for various climate conditions and for outdoor activities
- Total opening zipper easy and fast to clean
- High quality materials for a long lasting boot
- Padded rear flexors for an increased fitting comfort
- Rear leather pull-on loop
- Extremely comfortable for long-day usage (breathability is 400% better than EN20345 5.4.6 standard requirement)
- The heat insulation (sandbath test) is 30% higher than EN15090 6.3.1 standard requirements
- Excellent grip on uneven grounds (the outsole is 40% more durable than EN20345 5.8.3 standard requirement)
- The sole bonding strength is 90% higher than EN20345 5.3.1.2 standard requirements
- The energy absorption in the heel area is 100% higher than EN20345 6.2.4 standard requirements
- Outsole resistant to fuel oil



Product name: FIREGUARD EVOLUTION

Article number: 9081 GA

Upper leather

Full-grain cowhide leather, waterproofed, black, 2.4 - 2.6 mm thick

Top lining

Soft full-grain leather, waterproofed, black, 1.0-1.1 mm. thick

Lining

Seam sealed 4-ply laminate (GORE-TEX® DURACOM CAMBRELLE) bootie construction:

- Layer 1 Abrasion-proof lining Cambrelle® 100%PA
- Layer 2 Insulating felt for transporting water Vapour 100% PES
- Layer 3 Waterproof and water vapour permeable membrane ePTFE
- Layer 4 Backing fabric knit 100% PA

Reflecting insert

Reflex Scotchlite 3M material, yellow.

Toe cap

Very light aluminium toe cap (-40% compared to steel), asymmetric with supporting base, resistant to 200 Joule, manufactured and tested according to EN 12568. It is positioned between the leather upper and the lining, it can not be removed without damaging the whole boot. A plastic soft padding on the upper edge of the cap protects the feet while flexing.

Heel cap

1.8mm resinated synthetic bonded fabric, thermally mouldable, glued to upper material.

Upper cap

Abrasion-resistant flame-proof rubber mixture, black, 1.8 mm thick, glued to the upper leather using special PU cement

Ankle protection

Heat moulded material with shock-absorbing properties

Side antiperforation panels

Multilayer antiperforation fabric, with a perforation resistance of 1100 Newton.

Zip-closure

New Jolly rapid off-system with total opening zipper: the zip closure is made with the same leather quality of the upper and completed with 10 couples of nickel-free eyelets, non rusting, with a 5 mm inside diameter. The metal slider is running on plastic teeth, which are protected by leather on the front part.

Sewing thread

Kevlar® Filament, permanent flame-retardant, water-repellent finish, black.

Eyelets

Burnished brass, non rusting, 5 mm inside diameter.

Fixing hooks

Plastic hook with non-rusting metal pins, fixed with single rivet.

Laces

Meta-Aramid Filament (Nomex®) flat laces, 32 threads, fire-resistant treated

Lace-clip

At the ends of the lace are positioned 2 plastic clips with an inside spring system, to allow the optimum lace fixing.

Foot-bed

Anatomically shaped, made out of a layer of moisture transmitting felt (80% PES-20% VISCOSA), and with an upper covering made of anti abrasion non woven-material 100% PA. In the heel area is positioned an insert of EVA foam for the best comfort of the foot enabling to preserve the foot anatomy and to increase the energy absorption on the heel.

Insole

Average 5 mm thick insole made by a multilayer construction using special antiperforation composite materials with a plastic reinforcement as stabilizer and completed with a felt filler on the bottom. Textile antiperforation insoles, compared to the old style metal plates, offer considerable ergonomics and safety advantages: more protective surface, flexibility, insulation, humidity and impact absorption, reduced weight.

Sole

Nitrile rubber cemented sole, heat resistant at 300° C, antistatic, oil and petrol resistant, slip-resistant SRC, high wear-resistant. Self-cleaning and foreign objects + debris free granted by the peculiar structure of cleats and running surface. The high energy absorption in the heel area is given by the rubber compound of the outsole and by the height and shape of its cleats. The height and shape of its inner net, with air cushion, improve both shock absorbing but also thermal properties

Weight/pair

abt 2410 g (size 42)

Back height

abt 30 cm (suola inclusa) (size 42)

CE Certificate

EN 15090 :2006 F2A HI₃ CI AN - SRC Category III P.P.E

Size range

36 – 49 (50-51 supplied as specials)

