

2005/G Legend Low

MILITARY & POLICE



LEATHER
TRANSPIRATION
+310%

LONG LASTING SOLE
+20%

SOLE BONDING
STRENGTH
+85%

HEEL ENERGY
ABSORPTION
+80%

- Lightweight and comfortable police shoe
- Good stability both for walking and running
- Lining: GORE-TEX® Performance Comfort footwear, excellent for various climate conditions and for outdoor activities
- Highly breathable (breathability is 310% better than EN20347 5.4.6 standard requirement)
- Extremely comfortable for long-day usage
- Excellent grip on uneven grounds (the outsole is 20% more durable than EN20347 5.8.3 standard requirement)
- The sole bonding strength is 85% higher than EN20347 5.3.1.2 standard requirements
- The energy absorption in the heel area is 80% higher than EN20347 6.2.4 standard requirements
- Antistatic outsole resistant to fuel oil with cleated tread



GORE-TEX®
Performance
Comfort



Padded
collar



SRC
SRC
Certified

Product name: LEGEND LOW

Article number: 2005 G

Leather upper

Black full-grain cowhide leather, 1.6-1.8 mm thick, water-repellent, breathable treated, chrome-tanned and aniline dyed

Top lining

Soft black full-grain leather, 1.1-1.2 mm thick, water-repellent, breathable treated, chrome-tanned and aniline dyed

Lining

Seam sealed 4 ply laminate (GORE-TEX® DURACOM MS SPORTIVE), bootie construction:

Layer 1 warp knit 72%PA / 28% PES

Layer 2 functional no-woven 100% PES

Layer 3 bicomponent membrane based on ePTFE

Layer 4 backing fabric knit 100% PA

Toe cap

1.3 mm resinated synthetic bonded fabric, thermally mouldable.

Heel cap

1.8 mm resinated synthetic bonded fabric, thermally mouldable.

Sewing thread

Polyester 30/3, black, water-repellent treated

Lacing system

Round polyester laces, black, water-repellent treated, passing through 5 couples of rustproof burnished eyelets

Foot-bed

Anatomically shaped, 3,5 mm thick, made out of a layer of nonwoven material to absorb exceeding humidity, and with an upper covering made of anti abrasion nonwoven 100% PA.

Insole

Antistatic cellulose fibre, elastomeric bonded, 2.5 mm thick. In the heel area is positioned a polymeric material shank hold by a plastic reinforcement extending for 75% of the bottom surface.

Sole

Rubber sole, antistatic, oil and petrol resistant, with shock-absorbent heel. Resistant to contact heat (tested at 300°C) and non slip SRC.

Weight/pair

abt 1120 g (size 42)

Back height

abt 11 cm (sole included) (size 42)

CE certificate

EN ISO 20347:2004 O2 CI HI HRO WR FO - SRC Category II P.P.E.

Size range

36 - 49