


NEW

2011/GA City Mid

MILITARY & POLICE



- Comfort police shoe
- Metal-free
- Extremely light and comfortable, only 350 g each shoe
- Lining: GORE-TEX® Performance Comfort footwear, excellent for various climate conditions and for outdoor activities
- Good stability both for walking and running
- Highly breathable (breathability 600% higher than standard requirement)
- Extremely comfortable for long-day usage
- PU non-slip sole, resistant to fuel oil and with shock absorbing heel
- Antistatic



Product name: CITY MID

Article number: 2011 GA

Leather upper

Full-grain cowhide leather, waterproofed, black, 1.4-1.6 mm thick chrome-tanned and aniline dyed

Top lining

Soft full-grain leather, charcoal colour, 0.8 mm thick, padded with foam to improve fitting comfort

Lining

Seam sealed 4 ply laminate (GORE-TEX® LIGHT ROCK), bootie construction:
 Layer 1 warp knit 70%PA / 30% PES
 Layer 2 functional nonwoven 100% PES
 Layer 3 bicomponent membrane based on ePTFE
 Layer 4 backing fabric knit 100% PA

Toe cap

1.2 mm resinated synthetic bonded fabric, thermally mouldable.

Heel cap

1.6 mm resinated synthetic bonded fabric, thermally mouldable.

Sewing thread

Polyester 40/3, black, water-repellent treated.

Fastening system

8 mm polyester flat laces, black, water-repellent treated passing through 7 couples of reinforced holes.

Foot-bed

Anatomically shaped, made out of a layer of moisture transmitting felt (80% PES-20% VISCOSE), and with an upper covering made of anti abrasion non woven-material 100% PA. In the heel area is positioned an insert of EVA foam for the best comfort of the foot enabling to preserve the foot anatomy and to increase the energy absorption on the heel.

Insole

Antistatic felt 2.5 mm thick, with reinforced nylon shank.

Sole

Injected shock-absorbent PU, hydrolysis resistant, antistatic, oil - petrol and contact heat at 300°C resistant. Non slip and with high absorption in the heel area.

Weight/pair

abt 700 g (size 42)

Back height

abt 12 cm (sole included) (size 42)

CE certificate

EN ISO 20347:2007 O2 WR FO – SRA Category II P.P.E.

Size range

38 – 47