

NEW

2016/GA City Low

MILITARY & POLICE



2010/G



- Comfort police shoe
- Metal-free
- Extremely light and comfortable, only 330 g each shoe
- Lining: GORE-TEX® Extended Comfort footwear, excellent for temperate and hot climate
- Highly breathable
- Good stability both for walking and running
- Highly breathable (breathability 600% higher than standard requirement)
- Extremely comfortable for long-day usage
- PU non-slip sole, resistant to fuel oil and with shock absorbing heel
- Antistatic

**Product name:** CITY LOW**Article number:** 2016 GA**Leather upper**

Full-grain cowhide leather, waterproofed, black, 1.4-1.6 mm thick chrome-tanned and aniline dyed.

Top lining

Soft full-grain leather, charcoal colour, 0.8 mm thick, padded with foam to improve fitting comfort.

Lining

Seam sealed 3 ply laminate (GORE-TEX® MIAMI) foamed bootie construction:
 Layer 1 abrasion-proof lining 100%PA
 Layer 2 waterproof and water vapour permeable ePTE membrane
 Layer 3 backing fabric 100% PES and e fixing adhesive 100% PES

Toe cap

1.2 mm resinated synthetic bonded fabric, thermally mouldable.

Heel cap

1.6 mm resinated synthetic bonded fabric, thermally mouldable.

Sewing thread

Polyester 40/3, black, water-repellent treated.

Lacing system

8 mm polyester flat laces, black, water-repellent treated passing through 6 couples of reinforced holes.

Foot-bed

Anatomically shaped, made out of a layer of moisture transmitting felt (80% PES-20% VISCOSE), and with an upper covering made of anti abrasion non woven-material 100% PA. In the heel area is positioned an insert of EVA foam for the best comfort of the foot enabling to preserve the foot anatomy and to increase the energy absorption on the heel.

Insole

Antistatic felt 2.5 mm thick, with reinforced nylon shank.

Sole

Injected shock-absorbent PU, hydrolysis resistant, antistatic, oil - petrol and

contact heat at 300°C resistant. Non slip and with high absorption in the heel area.

Weight/pair

abt 660 g (size 42)

Back height

abt 11 cm (sole included) (size 42)

CE certificate

EN ISO 20347:2007 O2 WR FO – SRA Category II P.P.E.

Size range

38 – 47