

NEW

6060/GA Laser II

MILITARY & POLICE



6090/GA

LEATHER
TRANSPARATION
+400%

HEAT
INSULATION
+40%

LONG LASTING SOLE
+40%

SOLE BONDING
STRENGTH
+70%

HEEL ENERGY
ABSORPTION
+90%



- Lightweight and comfortable boot for Police
- Lining: GORE-TEX® Extended Comfort footwear, excellent for temperate and hot climate
- Good stability both for walking and running
- Highly breathable (breathability 400% higher than EN20347 5.4.6 standard requirement)
- Extremely comfortable for long-day usage
- Ankle protection
- Rear flexor to improve fitting comfort
- The heat insulation is 40% higher than EN20347 6.2.3.1 standard requirements
- Excellent grip on uneven grounds (the outsole is 40% more durable than EN20347 5.8.3 standard requirement)
- The sole bonding strength is 70% higher than EN20347 5.3.1.2 standard requirements
- The energy absorption in the heel area is 90% higher than EN20347 6.2.4 standard requirements
- Outsole resistant to fuel oil



GORE-TEX®
Extended
Comfort



Padded
collar and
flexor



Ankle
protection



Fast lacing
system



SOFT



Lightness



PU/RUBBER
sole

Product name: LASER II**Article number:** 6060 GA**Upper leather**

Full-grain cowhide leather, waterproofed, black, 1.8-2.0 mm thick.

Rear flexor

Soft leather, black, padded with special foam to improve fitting comfort.

Top lining

Calf leather, waterproofed, black, 1.0-1.1 mm thick

Lining

Seam sealed 3-ply laminate (GORE-TEX® VISION 3LY) bootie construction:

Layer 1: abrasion-proof lining 70% PA / 30% PES

Layer 2: waterproof and water vapour permeable ePTE membrane

Layer 3: Backing fabric knit 100% PA

Toe cap

1.8 mm resinated synthetic bonded fabric, thermally mouldable.

Heel cap

1.8 mm resinated synthetic bonded fabric, thermally mouldable.

Ankle protection

Heat moulded synthetic material

Sewing thread

Polyester 30/3, black, water-repellent treated

Lace hooks

New Jolly hooks made out of burnished rustproof steel.

Fixing hooks

Plastic hook with rustproof metal pins, for the optimum lace fixing.

Jointed open hooks

ZAMA alloy totally rustproof. The joints make lacing easier and faster.

Laces

Round polyester laces, black, water-repellent treated.

Foot-bed

Anatomically shaped, made out of a layer of moisture transmitting felt (80% PES-20% VISCOSE), and with an upper covering made of anti abrasion non woven-material 100% PA. In the heel area is positioned an insert of EVA foam for the

best comfort of the foot enabling to preserve the foot anatomy and to increase the energy absorption on the heel.

Insole

Abt 4 mm thick insole made out of special anti-perforation composite material. Textile antiperforation insoles, compared to the old style metal plates, offer considerable ergonomics and safety advantages: more protective surface, flexibility, insulation, humidity and impact absorption, reduced weight.

Sole

The sole construction is injected shock-absorbent PU with an antistatic oil and petrol resistant rubber running surface, resistant to contact heat at 300°C, with energy absorption in the heel area, slip-resistant. Self-cleaning and foreign objects + debris free granted by the peculiar structure of cleats and running surface.

Weight/pair

abt 1600 g (size 42)

Back height

abt cm.20 (sole included) (size 42)

CE certificate

EN ISO 20347:2004 O3 HI HRO WR FO AN - SRB Category II P.P.E.

Size range

36 - 47