

6508/GA Blackstorm

MILITARY & POLICE



LEATHER TRANSPARATION
+300%

HEAT INSULATION
+30%

LONG LASTING SOLE
+40%

SOLE BONDING STRENGTH
+90%

HEEL ENERGY ABSORPTION
+100%

- Anti riot blunt resistant and anti-ballistic features
- Good stability for operative needs
- Extremely breathable (breathability 300% higher than EN20345 5.4.6 standard requirement)
- Extremely comfortable for long-day usage
- Fast lacing system with easy roller eyelets
- Lining: GORE-TEX® Performance Comfort footwear, excellent for various climate conditions and for outdoor activities
- The heat insulation is 30% higher than EN20345 6.2.3.1 standard requirements
- Excellent grip on uneven grounds (the outsole is 40% more durable than EN20345 5.8.3 standard requirement)
- The sole bonding strength is 90% higher than EN20345 5.3.1.2 standard requirements
- The energy absorption in the heel area is 100% higher than EN20345 6.2.4 standard requirements
- Outsole resistant to fuel oil

GORE-TEX®
Performance
Comfort

J-Morphic

Fire
resistantPadded
collar and
flexorAnkle
protection

SOFT



ALU

Fast lacing
system

F.O.D.

100%
Kevlar®SRC
Certified**Product name:** BLACKSTORM**Article number:** 6508 GA**Upper**

Full-grain cowhide leather, waterproofed, black, 2.4- 2.6 mm and Meta-aramid (KEVLAR® Kleen) lined with Nomex® felt 4 mm thick, water-repellent treated.

Top lining

Soft aniline leather, waterproofed, black, 1.0-1.1 mm thick

Lining

Seam sealed 4 ply laminate (GORE-TEX® DURACOM CAMBRELLE), bootie construction:

Layer 1 Abrasion-proof lining Cambrelle® 100%PA

Layer 2 Functional nonwoven 100% PES

Layer 3 Waterproof and water vapour permeable ePTFE membrane

Layer 4 Backing fabric knit 100% PA

Toe cap

Very light aluminium toe cap (-40% compared to steel), asymmetric with supporting base, resistant to 200 Joule, manufactured and tested according to EN 12568. It is positioned between the leather upper and the lining; it can not be removed without damaging the whole boot.

A plastic soft padding on the upper edge of the cap protects the feet while flexing.

Heel cap

1.8 mm resinated synthetic bonded fabric, thermally mouldable.

Sewing thread

Kevlar® Filament, permanent flame-retardant, water-repellent finish, black.

Lace hooks

Burnished brass, non rusting, art. Easy Roller

Fixing hooks

Plastic hooks with non-rusting metal pins, for the optimum lace fixing.

Jointed open hooks

ZAMA alloy totally rustproof. The joints make lacing easier and faster.

Laces

Meta-Aramid filament (Nomex®) round laces, black, water-repellent treated.

Foot-bed

Anatomically shaped, made out of a layer of moisture transmitting felt (80% PES-20% VISCOSA), and with an upper covering made of anti abrasion non woven-material 100% PA. In the heel area is positioned an insert of EVA foam for the best comfort of the foot enabling to preserve the foot anatomy and to increase the energy absorption on the heel.

Insole

Average 5 mm thick insole made by a multilayer construction using special antiperforation nylon materials with a plastic reinforcement as stabilizer and completed with felt filler on the bottom.

Textile antiperforation insoles, compared to the old style metal plates, offer considerable ergonomics and safety advantages: more protective surface, flexibility, insulation, humidity and impact absorption, reduced weight.

Sole

Nitrile rubber cemented sole, heat resistant at 300° C, antistatic, oil and petrol resistant, with energy absorption in the heel area, slip-resistant SRC. Self-cleaning and foreign objects + debris free granted by the peculiar structure of cleats and running surface.

Thanks to the double density of the rubber compound, the shock absorption and the slip resistance are considerably improved.

Weight/pair

abt 1960 g (size 42)

Back height

abt 23 cm (sole included) (size 42)

CE certificate

EN ISO 20345:2004 S3 HRO HI CI WR CR Category III P.P.E

Size range

36 – 49 (50-51 supplied as specials)