# 650/GA Parade 4S Lady

**MILITARY & POLICE** 



710/GS







- Female uniform décolleté, extremely light and comfortable
- Highly breathable (breathability is 500% better than EN20347 5.4.6 standard requirement)
- New last with wider ball girth and improved ergonomic features to offer better performances
- · New full grain goat leather perforated foot-bed
- 4,5 cm heel made of noiseless polystyrene with high impact resistance
- Under-heel made of TPU with high tear and abrasion resistance
- Lining: GORE-TEX® Extended Comfort footwear, excellent for temperate and hot climate
- The outsole is 100% more durable than standard requirement
- The sole bonding strength is 90% higher than standard requirements
- Ultimate energy absorption with PORON® shock absorber system
- Antistatic





Real leather sole









Product name: PARADE 4S LADY
Article number: 650 GA

#### Upper leather

Black full-grain calfskin, thickness 1.4-1.6 mm water-repellent and breathable treated, chrome-tanned and aniline dyed

# Lining

Seam sealed 3 ply laminate (GORE-TEX® MIAMI) "bottom filler" construction:

Layer 1: abrasion-proof lining 100%PA
Layer 2: waterproof and water vapour permeable ePFTE membrane

Layer 3: backing fabric 100% PES and e fixing adhesive 100% PES

# Toe cap

Extruded polyurethane and synthetic fibres impregnated with heat-setting resins, thickness of 0.7 mm.

# Heel cap

Regenerated leather impregnated with heat-setting resins, thickness 1.6 mm.

# Sewing thread

Polyester 30/3, black, water-repellent treated

#### Foot-bed

Full grain goat leather with a Poron® insertion 3,00 mm thick.

#### Insole

Synthetic fibres impregnated with heat-setting resins, with metallic shank and rear reinforcement.

#### Sole

Genuine leather midsole to which a half sole made of special anti-static, non slip, rubber is glued.

The heel, height of abt 4,5 cm, is made out of shock absorbent polystyrene and TPU tread.

# Weight/pair

abt 500 g (size 37)

#### Back height

abt 11 cm (sole included) (size 37)

#### CE certificate

UNI EN ISO 20347:2008 OB A WRU WR - SRB Category II P.P.E.

#### Size range

35 - 42

