

7006/G Motor Guard

MILITARY & POLICE



LEATHER TRANSPARATION
+650%

SOLE BONDING STRENGHT
+50%

HEEL ENERGY RESORPTION
+15%

- Police M/C boot
- Maximum waterproofness in every climate condition (breathability is 650% higher than EN347/1 4.4.6 standard requirements)
- Lightweight and comfortable with functional zipper and velcro fastening system
- Good stability both for walking and motorcycling
- Ankle protection
- Excellent grip on urban grounds
- Lining: GORE-TEX® Performance Comfort footwear, excellent for various climate conditions and for outdoor activities
- Extremely comfortable for long-day usage
- The sole bonding strength is 50% higher than EN347/1 4.3.1.2 standard requirements
- The energy absorption in the heel area is 15% higher than EN347/1 4.3.6 standard requirements



Product name: MOTOR GUARD

Article number: 7006 G

Upper material

Full-grain cowhide leather, waterproofed, black, 1.8 - 2.0 mm thick

Front flexor

Soft imitation leather, waterproofed, black, 1.0 – 1.1 mm thick

Lining

Seam sealed 4 ply laminate (GORE-TEX® DURACOM CAMBRELLE), bootie construction:

Layer 1 Cambrelle fabric 100% PA

Layer 2 functional nonwoven 100% PES

Layer 3 waterproof and water vapour permeable ePFTE membrane

Layer 4 backing fabric knit 100% PA

Reflecting insert

Side band 2 cm wide of top quality reflecting material coated with transparent plastic material.

Elastic band

Positioned in the rear part of the boot to improve fitting comfort.

Toe cap

1.3 mm nonwoven resinated synthetic bonded material, thermally mouldable.

Heel cap

1.8 mm non-woven resinated synthetic bonded material, thermally mouldable.

Ankle and shin protection

Heat moulded synthetic material with shock-absorbing properties, 2.5 mm thick

Shift pad

Made out of soft 100% PU

Zipper

8 mm wide, with plastic teeth

Sewing thread

Polyester thread, 30/3 title, water-repellent treated, black.

Foot-bed

Anatomically shaped, moisture transmitting felt sole, abt 3,5 mm thick. Lined on top with abrasion resistant 100% PA.

Insole

Made out of special nonwoven antistatic material with metallic shank.

Sole

Rubber sole, antistatic, oil and petrol resistant. Non-slip, wear and contact heat (tested at 300°C) resistant.

Fastening system

First quality velcro material

Weight/pair

abt 1450 g (size 42)

Back height

cm. 30 (sole included) (size 42)

CE certificate

EN 347-1 A WRU E ORO CI WR HRO Category II P.P.E.

Size range

36 – 48