

NEW

6100/GA Dragon Fly

SEARCH & RESCUE OPERATORS
AND FIRE FIGHTER VOLUNTEERS

- Also suitable for Military and Police.



- Safety footwear for civil protection and Police
- Highly breathable (breathability 500% higher than EN20347 5.4.6 standard requirement)
- Extremely versatile high quality comfortable shoe suitable for outdoor activities
- Metal free
- Lightweight and comfortable
- Good stability both for walking and running also on uneven grounds
- Lining: GORE-TEX® Performance Comfort footwear, excellent for various climate conditions and for outdoor activities
- Extremely comfortable for long-day usage
- New last with larger ball girth
- Extremely light thanks to its new PU-rubber sole
- New rapid lacing system with extra resistant laces and plastic eyelets
- Outsole resistant to fuel oil with antiperforation insole; bonding strength is 70% higher than EN20347 5.3.1.2 standard requirements; SRC slip resistance.

**Product name:** DRAGON FLY**Article number:** 6100 GA**Leather upper**

Full-grain cowhide leather, waterproofed, black, 1.4-1.6 mm thick

Toe cap

1.8 mm resinated synthetic bonded fabric, thermally mouldable.

Lining

Seam sealed 4 ply laminate (GORE-TEX® Light Rock), foamed bootie construction:

Layer 1 warp knit 70%PA / 30% PES

Layer 2 functional nonwoven 100% PES

Layer 3 Waterproof and water vapour permeable membrane ePTFE

Layer 4 backing fabric knit 100% PA

Heel cap

1.8 mm resinated synthetic bonded fabric, thermally mouldable.

Sewing thread

Polyester thread, 30/3 title, water-repellent treated, black

Rear loop

Polyamide fabric moulded loop 15 mm wide

Lacing system

4 couples of polyamide fabric moulded loops 10 mm wide and 1 couple of polymeric material eyelets

Laces

Round laces, black, water-repellent treated, minimum diameter 4 mm

Insole

Abt 4 mm thick insole made out of special anti-perforation composite material.

Textile antiperforation insoles, compared to the old style metal plates, offer considerable ergonomics and safety advantages: more protective surface, flexibility, insulation, humidity and impact absorption, reduced weight.

SoleInjected shock-absorbent PU with density lower than 0.50 g/cm³ with an antistatic oil and petrol resistant 2.50mm thick rubber running surface, resistant to contact heat at 300°C, hydrolysis and non slip thanks to its 5.0 mm high self cleaning cleats.**Weight/pair**

abt 1220 g (size 42)

Back height

abt 13 cm (sole included) (size 42)

CE certificate

EN ISO 20347:2004 / A1:2007 – O3 HRO WR FO - SRC Category II P.P.E.

Size range

36 – 48