# 2250/GA Chamoix

#### · Also suitable for Search & Rescue operators and fire fighter volunteers.

WORKWEAR



• Professional trekking footwear for first aid operators, territory surveillance activities and hunting.

- Extremely comfortable for long-day usage
- Extremely breathable (breathability 400% better than EN20347 5.4.6 standard requirement)
- The new combined stabilizing system in the heel assures an excellent grip on uneven and rocky grounds, thus also improving the energy absorption and granting more reactivity during walking
- Lining: GORE-TEX<sup>®</sup> Performance Comfort footwear, excellent for various climate conditions and for outdoor activities
- · Antiperforation composite insole
- Cover-band for protection against rocks and debris.
- The heat insulation is 30% higher than EN20347 6.2.3.1 standard requirements

• Excellent grip on wet surfaces thanks to Vibram Fourracon sole; the sole bonding strength is 20% higher than EN20347 5.3.1.2 standard requirements

- High absorption PU midsole (energy absorption in the heel area is 50% higher than EN20347 6.2.4 standard requirements
- Antistatic and heat resistant 300° C outsole. Resistant to fuel oil



Product name: CHAMOIX

Article number: 2250 GA

### Leather upper

Dark brown nubuck cowhide leather, 2.4 - 2.6 mm thick, waterproof, chrometanned and aniline dyed.

#### Top lining

Dark brown nubuck cowhide leather, 1.0-1.2 mm thick, water-repellent and breathable treated.

#### Lining

Seam sealed 4 ply laminate (GORE-TEX® DURACOM CAMBRELLE), bootie construction:

Layer 1 Abrasion-proof lining Cambrelle® 100%PA

Layer 2 Functional nonwoven 100% PES

Layer 3 Waterproof and water vapour permeable membrane ePTFE Layer 4 Backing fabric knit 100% PA

#### Toe cap

1.8 mm resinated synthetic bonded fabric, thermally mouldable.

#### Heel cap

1.8 mm resinated synthetic bonded fabric, thermally mouldable.

## Cover-band

Abrasion and impact resistant flame-proof special rubber mixture, black, 1.8 mm thick, glued to the upper leather using special PU cement.

#### Sewing thread

Polyester 30/3, black, water-repellent treated

#### Lacing system

Round polyester laces, brown, water-repellent treated, passing through 5 couples of burnished eyelets, 1 couple of fixing hooks and three couples of open hooks on top. All hooks made of rustproof brass/steel.

#### Foot-bed

Anatomically shaped, 3,5 mm thick, made out of a layer of nonwoven material to absorb exceeding humidity, and with an upper covering made of black Cambrelle fabric.

#### Insole

LEATHE

Made out of antiperforation lightweight and durable HT ceramized fabric Textile antiperforation insoles, compared to the old style metal plates, offer considerable ergonomics and safety advantages: more protective surface, flexibility, insulation, humidity and impact absorption, reduced weight. **Sole** 

# Bicomponent sole composed by a soft shock-absorbent PU wedge-heel and Vibram rubber running surface, self-cleaning, antistatic, resistant to oil and petrol, contact heat at 300°C, non slip with energy absorption insert in the heel area.

Weight/pair

#### abt 1760 g (size 43)

Back height

abt 18 cm (sole included) (size 43)

#### CE certificate

EN ISO 20347:2004 / A1:2007 O3 HI WR AN HRO FO - SRA Category II P.P.E. Size range

#### 38 – 48

